

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Spray Contact Adhesive P125
UFI : N300-80X6-X00Q-CEH7
Type of product : Contact adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial uses, Professional use
Industrial/Professional use spec : Contact adhesive

1.2.2. Uses advised against

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Details of the supplier of the safety data sheet

Distributor

SealEco
Kävsjövägen 38
P.O. Box P.O. Box 514, 331 25 Värnamo
331 35 Värnamo - SWEDEN
T +46 (0) 370 510 100 - F +46 (0) 370 510 101
info@sealeco.com - www.sealeco.com

1.4. Emergency telephone number

Emergency number : +46 8 33 12 31 (International) 112 (National)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful by prolonged exposure. Dangerous for the environment.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Danger

Contains :

cyclohexane; Aliphatic hydrocarbons; acetone; propan-2-one; propanone

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H400 - Very toxic to aquatic life. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting equipment. P261 - Avoid breathing vapours, spray. P264 - Wash hands, forearms and face thoroughly after handling.

2.3. Other hazards

Other hazards which do not result in classification : Vapour mixes readily with air, forming explosive mixtures.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2 (EC Index-No.) 601-017-00-1 (REACH-no) 01-2119463273-41	20 – 30	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Aliphatic hydrocarbons	(EC-No.) 921-024-6 (REACH-no) 01-2119475514-35	20 – 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	10 – 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Take victim to a doctor if irritation persists.
First-aid measures after inhalation	: Remove victim to fresh air. If not breathing, give artificial respiration. When there is no quick recovery : consult a doctor/medical service.
First-aid measures after skin contact	: Rinse with water. Wash with water and soap. Take victim to a doctor if irritation persists. Repeated or prolonged skin contact may cause dermatitis and defatting.
First-aid measures after eye contact	: Rinse with plenty of water. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: In all cases of doubt, or when symptoms persist, seek medical attention. Do not induce vomiting.

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Dizziness. Nausea. Dry skin. Headache. Unconsciousness. skin irritation.
Symptoms/effects after skin contact	: Harmful when absorbed into the body through the skin. ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: May produce an allergic reaction. Irritating to skin. May cause skin irritation / dermatitis.
Symptoms/effects after eye contact	: Irritating to eyes. Pain. Redness of the eye tissue.

4.3. Indication of any immediate medical attention and special treatment needed

Contains: petrol. Causes damage to the central nervous system.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Carbon dioxide. Water haze. Carbon dioxide. Powder. Foam. Sand. sand/earth.
Unsuitable extinguishing media	: Do not use a high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: May form flammable en explosive vapour-air mixture. Possible ignition from a distance. Will float and can be reignited on water surface.
Explosion hazard	: Atex klasse IIA, T3.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate unnecessary personnel.
Firefighting instructions	: Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Ensure adequate air ventilation. When handling product, avoid contact with skin and eyes. No naked flames or sparks. In order to rule out potential electrostatic discharge production, the system must be adequately grounded. Do not inhale vapour. Stop engines and no smoking. Stop leak if safe to do so.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Use protective clothing. See Heading 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing and gloves. Wear a self contained breathing apparatus.
Emergency procedures	: Ventilate area. Stop leak if safe to do so. Stop release.

6.2. Environmental precautions

Substance must not be discharged into the sewer.

6.3. Methods and material for containment and cleaning up

For containment	: Shut off leaks if without risks. Contain released substance, pump into suitable containers. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
Methods for cleaning up	: Wash down leftovers with plenty of water.
Other information	: May form flammable vapour-air mixture.

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

Exposure controls and personal protection. See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: if necessary: Ventilation, local exhaust, or breathing protection. In use, may form flammable vapour-air mixture. Handle empty containers with care because residual vapours are flammable. ventilate the area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. No naked flames, sparks, and do not smoke. Do not handle until all safety precautions have been read and understood. Keep away from ignition sources (including static discharges). Provide good ventilation in process area to prevent formation of vapour. Take precautionary measures against static discharge.
Handling temperature	: 8 – 30 °C
Hygiene measures	: Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Use explosion-proof electrical/ventilating/lighting equipment. Provide adequate ventilation.
Storage conditions	: Store in original container. Keep container tightly closed.
Incompatible materials	: Direct sunlight. Heat sources. Sources of ignition.
Maximum storage period	: 12 months
Storage temperature	: 8 – 25 °C
Storage area	: Keep container tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Fireproof storeroom. Keep only in the original container.
Special rules on packaging	: meet the legal requirements.

7.3. Specific end use(s)

Contact adhesive.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

cyclohexane (110-82-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	700 mg/m ³
IOEL TWA [ppm]	200 ppm
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	700 mg/m ³
MAK (OEL TWA) [ppm]	200 ppm
MAK (OEL STEL)	2800 mg/m ³
MAK (OEL STEL) [ppm]	300 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	350 mg/m ³
OEL TWA [ppm]	100 ppm

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

cyclohexane (110-82-7)	
France - Occupational Exposure Limits	
VME (OEL TWA)	700 mg/m ³
VME (OEL TWA) [ppm]	200 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	700 mg/m ³
AGW (OEL TWA) [2]	200 ppm
AGW (OEL C)	800 mg/m ³
AGW (OEL C) [ppm]	2800 ppm
Netherlands - Occupational Exposure Limits	
MAC-TGG (OEL TWA) [ppm]	700 ppm

Aliphatic hydrocarbons	
France - Occupational Exposure Limits	
VME (OEL TWA)	1000 mg/m ³
VLE (OEL C/STEL)	1500 mg/m ³

acetone; propan-2-one; propanone (67-64-1)	
Belgium - Occupational Exposure Limits	
OEL TWA	1210 mg/m ³ 2009
OEL TWA [ppm]	500 ppm 2009
OEL STEL	2420 mg/m ³ 2009
OEL STEL [ppm]	1000 ppm 2009
Netherlands - Occupational Exposure Limits	
MAC-TGG (OEL TWA)	1210 mg/m ³ 2007
MAC-TGG (OEL TWA) [ppm]	510 ppm 2007
MAC-15 (OEL STEL)	2420 mg/m ³ 2007
MAC-15 (OEL STEL) [ppm]	1020 ppm 2007

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

In case of inadequate ventilation wear respiratory protection. Ensure adequate ventilation.

8.2.2. Personal protection equipment

Personal protective equipment:

In case of splash hazard: safety glasses. Gloves.

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Standard working clothes

Hand protection:

protective gloves

Other skin protection**Materials for protective clothing:**

synthetic material. latex. polyethylene/ethylenevinyalcohol. PVC. synthetic rubber

8.2.2.3. Respiratory protection

Respiratory protection:

Ensure adequate ventilation. If local exhaustion is insufficient, wear full-face mask.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

See section 6,7, 12 en 13.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Red to red-brown.
Odour	: Aromatic odour.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55 °C
Flash point	: -26 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 160 hPa 20°C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,81 g/cm ³ ± 0.05
Solubility	: Water: insoluble in water

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 308 – 285 mm ² /s
Viscosity, dynamic	: 250 – 350 mPa·s (20°C Spindel 4 20RPM)
Explosive properties	: Product is not explosive but may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Explosive limits	: 1,1 – 7,4 vol %

9.2. Other information

VOC content	: 60 – 62 %
Other properties	: Contains volatile component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Vapours may form flammable and explosive mixture with air.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

fire, naked flames. sparks. Heat. direct sunlight.

10.5. Incompatible materials

When liquid avoid. Water.

10.6. Hazardous decomposition products

On heating/burning: release of harmful products.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

cyclohexane (110-82-7)

LD50 oral rat	> 5000 kilogram
LD50 dermal rat	> 2000 mg/kg

Aliphatic hydrocarbons

LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25,2 mg/l air Animal: rat

acetone; propan-2-one; propanone (67-64-1)

LD50 oral rat	> 5000 mg/kg
---------------	--------------

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD50 dermal rat	> 15000 mg/kg
LC50 Inhalation - Rat	76 mg/l/4h

Skin corrosion/irritation	: Irritant to the skin. Repeated exposure may cause skin dryness or cracking
Serious eye damage/irritation	: Eye irritation
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Aliphatic hydrocarbons

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

acetone; propan-2-one; propanone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Spray Contact Adhesive P125

Viscosity, kinematic	308 – 285 mm ² /s
----------------------	------------------------------

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Floats on water, evaporates quickly, danger of pollution of drinking water when large quantities of the product enters the soil. . Avoid undiluted product to come into sewer or superficial water.
Ecology - water	: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.

cyclohexane (110-82-7)

LC50 - Fish [1]	4,53 mg/l (Pimephales promelas)
EC50 - Crustacea [1]	0,9 mg/l 48h
EC50 - Other aquatic organisms [1]	3,4 mg/l 72h (Selenastrum capricornutum)

Aliphatic hydrocarbons

LC50 - Fish [1]	1 – 10 mg/l
LC50 - Other aquatic organisms [1]	1 – 10 ml/l Algae
EC50 - Other aquatic organisms [1]	1 – 10 mg/l Bacteria
LOEC (chronic)	0,32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

acetone; propan-2-one; propanone (67-64-1)

LC50 - Fish [1]	> 5000 mg/l 96u
EC50 - Crustacea [1]	> 10000 mg/l 48u

12.2. Persistence and degradability

cyclohexane (110-82-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Aliphatic hydrocarbons

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

acetone; propan-2-one; propanone (67-64-1)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

cyclohexane (110-82-7)

Partition coefficient n-octanol/water (Log Pow)	3,4
Bioaccumulative potential	None reasonably foreseeable.

acetone; propan-2-one; propanone (67-64-1)

Partition coefficient n-octanol/water (Log Pow)	-0,24
Bioaccumulative potential	There is no bioaccumulation.

12.4. Mobility in soil

cyclohexane (110-82-7)

Ecology - soil	Insoluble in water.
----------------	---------------------

Aliphatic hydrocarbons

Ecology - soil	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
----------------	---

12.5. Results of PBT and vPvB assessment

Component

cyclohexane (110-82-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone; propan-2-one; propanone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information : Handle uncleaned empty containers as highly flammable and dangerous.

SECTION 14: Transport information

In accordance with ADR

14.1 UN number

UN-No. (ADR) : UN 1133

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ADHESIVES
Transport document description (ADR) : UN 1133 ADHESIVES, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3

Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : II

14.5. Environmental hazards


Dangerous for the environment : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 640D
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E2
Packing instructions (ADR) : P001, IBC02, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions (ADR) : TP1, TP8
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Special provisions for carriage - Operation (ADR) : S2, S20
Hazard identification number (Kemler No.) : 33
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
3(a)	Spray Contact Adhesive P125 ; cyclohexane ; Aliphatic hydrocarbons ; acetone; propan-2-one; propanone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Spray Contact Adhesive P125 ; cyclohexane ; Aliphatic hydrocarbons ; acetone; propan-2-one; propanone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Spray Contact Adhesive P125 ; cyclohexane ; Aliphatic hydrocarbons	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Spray Contact Adhesive P125 ; cyclohexane ; Aliphatic hydrocarbons ; acetone; propan-2-one; propanone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.
57.	cyclohexane	Cyclohexane

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 60 – 62 %

15.1.2. National regulations

France

Occupational diseases

Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting : None of the components are listed

giftige stoffen – Vruchtbaarheid

Spray Contact Adhesive P125

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Data sources : The information supplied has been based upon the current level of information available, for the purpose of specifying the requirements regarding environment, health and safety in conjunction with the product. They are not to be interpreted as a warranty.

Other information : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.