

Product Specification

Prelasti S/ST

Prelasti S/ST (Standard/Standard Thermobond) is an elastomeric waterproofing membrane based on the rubber polymer EPDM. Prelasti S/ST shall be used as waterproofing layer in roof constructions under ballast, mechanical attached or adhered to the substrate. Prelasti provide very long expected service life and is an environmental friendly product.



Technical data

Weight 1.2 mm: 1.3 kg/m²
 1.5 mm: 1.7 kg/m²

Product	Thickness (mm)	Width (m)	Length (m)
Standard panels Prelasti S/ST	1.2 / 1.3 / 1.5	3.36	25
	1.2 / 1.3 / 1.5	5.02	25
	1.2 / 1.3 / 1.5	6.68	25
	1.2 / 1.3 / 1.5	8.34	25
	1.2 / 1.3 / 1.5	10.00	25
	1.2 / 1.3 / 1.5	11.66	25
	1.2 / 1.3 / 1.5	13.32	25
	1.2 / 1.3 / 1.5	14.98	25
Prefabricated made to measure panels	1.2 / 1.3 / 1.5	Specified by customer	Specified by customer
Rolls	1.2 / 1.3 / 1.5	1700	1.2 mm: 25 m / 100 m 1.3 mm: 25 m / 80 m 1.5 mm: 25 m / 75 m

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life. Please contact your local Sales department for information regarding packaging sizes.

Approvals, Certificates & Specifications

CE: EN 13956, KOMO, BBA, Dubokeur, ATG. More approvals are available upon request.



DUBOKEUR



Product Specification

Prelasti NO FLAME FR / NO FLAME FRT

Prelasti NO FLAME FR / NO FLAME FRT are elastomeric waterproofing membranes based on the rubber polymer EPDM. Prelasti NO FLAME FR / NO FLAME FRT shall be used as waterproofing layer in roof constructions mechanical attached or adhered to the substrate. The prefabrication provides quicker and safer installation. Prelasti NO FLAME FR / NO FLAME FRT are flame retardant and classified as Broof (T1, T2, T4). Prelasti provide very long expected service life and is an environmental friendly product.



Technical data

Weight 1.2 mm: 1.49 kg/m²
1.5 mm: 1.86 kg/m²

Product	Thickness (mm)	Width (m)	Length (m)
Standard panels Prelasti NO FLAME FR/FRT	1.2 / 1.3 / 1.5	3.36	25
	1.2 / 1.3 / 1.5	5.02	25
	1.2 / 1.3 / 1.5	6.68	25
	1.2 / 1.3 / 1.5	8.34	25
	1.2 / 1.3 / 1.5	10.00	25
	1.2 / 1.3 / 1.5	11.66	25
	1.2 / 1.3 / 1.5	13.32	25
	1.2 / 1.3 / 1.5	14.98	25
Prefabricated made to measure panels	1.2 / 1.3 / 1.5	Specified by customer	Specified by customer
Rolls	1.2 / 1.3 / 1.5	1700	1.2 mm: 25 m / 80 m 1.3 mm: 25 m / 75 m 1.5 mm: 25 m / 65 m

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life. Please contact your local Sales department for information regarding packaging sizes.

Approvals, Certificates & Specifications

CE: EN 13956, KOMO, ATG, Fire classification Broof (T1, T2, T4). More approvals are available upon request.



SealEco

Post Address: P.O. Box 514, SE-331 25 Värnamo, Sweden