

Product Specification

Primer 9800

Polymer based primer for consequent use with self-adhesive SealEco rubber membranes, and for priming porous substrates.

Technical data

| | |
|-----------------------------|---|
| Base: | Primer based on a synthetic rubber and synthetic resins, dissolved in inflammable organic solvents. |
| Colour: | Black |
| Flash point: | <0°C |
| Viscosity (at 20°C): | 900 ±100 Pa.s |
| Solids: | 36,3 % |
| Density (at 20°C): | 840 ±10 kg/m³ |
| Shelf life: | 12 months if stored cool in unopened original packing. To best ored in a well ventilated place. |



Packaging

| | | | | |
|-------------|---------------------------|------------|---------------|-----------------|
| 1.07L/can | 0,9 kg/can | 12 can/box | 30 box/pallet | 324,0 kg/pallet |
| 5,0 L/can | 4,2 kg/can | | 96 can/pallet | 403,2 kg/pallet |
| 14,88 L/can | 12,5 kg/can | | 33 can/pallet | 412,5 kg/pallet |
| | 14,4 kg pressure canister | | 24 can/pallet | 345,6 kg/pallet |

Consumption

125-250 g/m² depending on substrate.

Application instructions

Primer 9800 is ready-for-use and must not be thinned or mixed with other products. The material and the substrate to be glued must be dry and clean. Primer 9800 should be applied in a thin even layer with a stiff brush or a finely-toothed spatula (exc. sprayable version). Before unrolling the membrane, check that the primer is totally flashed of. Max open time is 3 hours. Primer 9800 may only be used in dry weather-conditions, no moisture must be enclosed between the primer-layer and the selfadhesive membrane. When Primer 9800 was exposed to precipitation, moisture, dirt, a new layer shall be applied. Equipment and tools can be cleaned with Cleaning Wash 9700. Application temperature: Min. 5°C

Substrate

Type: Concrete, wood, metal or insulation with facing intended for bonding (check technical data sheet insulation). Primer 9800 is not suitable as a primer for Polystyrene foam and plasticized PVC foil.

Warning

Primer 9800 is highly flammable. Keep away from open fire.
Read the Material safety data sheet before use.