

Product Specification

Prelasti Fleece FR/FRT

Prelasti Fleece FR/FRT is a fleece reinforced roofing membrane for use for exposed roofs either mechanically attached or adhered to substrate with adhesives or bonding bitumen. The product has external fire performance classification B_{ROOF}(t1,2,4). Seaming is performed with hot air enabled by patented Thermobond technology or with Tape System.

Technical data

Weight: 2.3 mm: 1.9 kg/m²

Effective thickness: 2.3 mm: 1.3 mm

Article	Thickness (mm)	With (mm)	Length (mm)	Seam type	Width packaging
Prelasti Fleece FRT	2.3	1.74	20	T edge 40 mm	15 rolls/pallet
Prelasti Fleece FRT	2.3	1.34	20	T edge 40 mm	15 rolls/pallet
Prelasti Fleece FRTT	2.3	1.38	20	2 T egdes 40 mm	15 rolls/pallet
Prelasti Fleece FR	2.3	1.78	20	Free Tape edge 80 mm	15 rolls/pallet
Prelasti Fleece FR	2.3	1.71	20	No edge	15 rolls/pallet

*Availability depending on country and supplier.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

CE EN 13956:2012

BBA approval

B_{ROOF} t1,t2,t4 classifications on demand