

# Product Specification

## RubberTop Fleece S

RubberTop Fleece S is a fleece reinforced roofing membrane for use for exposed roofs either mechanically attached or adhered to substrate with adhesives or bonding bitumen. The product has external fire performance classification B<sub>ROOF</sub>t1 and B<sub>ROOF</sub>t2.

All seaming is performed with Tape System.



### Technical data

Weight: 2.3 mm: 1.8 kg/m<sup>2</sup> 2.5 mm: 2,1 kg/m<sup>2</sup>  
 Effective thickness: 2.3mm: 1.3mm 2.5mm: 1.5mm

Article	Thickness (mm)	Width (mm)	Length (mm)	Seam type	Width/packageing
RubberTop Fleece S	2.3	1.78	20	Free Tape edge 80mm	15/6 rolls/pallet
RubberTop Fleece S	2.3	1.71	20	No edge	15/6 rolls/pallet
RubberTop Fleece S	2.3	3.78	20	Free Tape edge 80 mm	10 rolls/pallet*

\* Availability depending on country and supplier – packed on pallet 3.50m x 1.20m

### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

### Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

### Approvals, Certificates & Specifications

CE EN 13956:12

B<sub>ROOF</sub> t1,t2 classifications on demand

