

# Product Specification

## Cover Tape

Cover Tape is used for connecting and joining SealEco EPDM membranes. It can also be used for repairs and details in two dimensions and covering mechanically fastened bars. Cover Tape is flexible and provides immediate adhesion when in contact with the membrane. The product should always be used in conjunction with Single Ply Primer.

### Technical data

<b>Base:</b>	Synthetic Rubber	
<b>Colour:</b>	Black	
<b>Thickness:</b>	1.14 mm	

### Packaging

<b>Width:</b>	152 mm	305 mm
<b>Roll length:</b>	30.5 m	15.3 m
<b>Rolls/case:</b>	2 pcs	1 pce
<b>Weight/case:</b>	23.6 kg	12.2 kg
<b>Cases/pallet:</b>	18 pcs	36 pcs



\* Note: not all widths are available in different countries.

### Storage

Store in a dry and cool place (5°C-30°C) in original packaging.  
Shelf life: 9 months in original packaging.

### Direction for use

The EPDM membranes to be connected should be dry, clean and free from creases or tension. If necessary, the EPDM membrane can be cleaned with Cleaning Wash 9700 before joining. Using a marker pen or chalk, mark the position of the location of the Cover Tape. Apply Single Ply Primer with a scrub pad over the entire area to be joined. Wait for the Primer to flash off so that it is dry to the touch but still tacky. Do not leave exposed for longer than 20 minutes (at 20°C, 50% RV).

Unroll the Cover Tape and press firmly using a 50mm wide silicone seam roller. Apply pressure from the middle of the tape to the edge to eliminate any trapped air. Seal all cut edges with Sealant 5590. Consult the technical manual for further instructions.

### Limitations

Cover Tape should not be installed in temperatures below +5°C and above 40°C; during rain, mist or where there is a risk of condensation or strong winds.

### Safety

Please read the safety data sheet before use.