



## DECLARATION OF PERFORMANCE

RubberTop FR

N° DOP RubberTop FR-2020.02.24

**1. Unique identification code of the product type:**

RubberTop FR.

**2. Identification of the construction product:**

See product label and/or packaging.

**3. Intended use or uses:**

RubberTop FR is an unreinforced elastomeric waterproofing membrane, EPDM polymer based, produced in two ply. The product comes in black colour and has a surface texture on both sides. The range of use is waterproofing of roofs.

**4. Contact address of manufacturer/trading company:**

SealEco AB  
P.O.Box 514  
SE-331 25 Värnamo  
Sweden

**5. System or systems of assessment and constancy of performance:**

System 2+.

**6. Notified body / Certification n°:**

Notified body: 0958 SGS INTRON Certificatie BV  
FPC: 0958-CPR-2036/1

## 7. Declared performance

| Characteristic            | Test method               | Unit              | Performance             |                 | Harmonised Standard |
|---------------------------|---------------------------|-------------------|-------------------------|-----------------|---------------------|
|                           |                           |                   | Value                   | Expr. of result |                     |
| Water tightness           | EN 1928 (B)               | 10 kPa            | Pass                    | Pass/Fail       | EN 13956:2012       |
| Tensile strength          | EN 12311-2                | N/mm <sup>2</sup> | 7                       | ≥ MLV           |                     |
| Elongation at break       | EN 12311-2 (B)            | %                 | 300                     | ≥ MLV           |                     |
| Root resistance           | EN 13948/FLL              |                   | NPD                     | Pass/Fail       |                     |
| Resistance to static load | EN 12730 (A/B)            | kg                | 15                      | ≥ MLV           |                     |
| Resistance to impact      | EN 12691 (B)              | mm                | 1000                    | ≥ MLV           |                     |
| Tear resistance           | EN 12310-2                | N                 | 50                      | ≥ MLV           |                     |
| Peel strength of joint    | EN 12316-2                | N/50 mm           | 50                      | ≥ MLV           |                     |
| Shear strength of joint   | EN 12317-2                | N/50 mm           | 200                     | ≥ MLV           |                     |
| Durability                | EN 1297                   | Classification    | Pass                    | Pass/Fail       |                     |
| Foldability               | EN 495-5                  | °C                | -40                     | > MLV           |                     |
| External fire performance | EN 13501-5                |                   | F <sub>ROOF</sub> (t)   | Classification  |                     |
| Reaction to fire          | EN 13501-1                |                   | Class E                 | Classification  |                     |
| Dangerous substances      | EU construction directive |                   | No dangerous substances | MDV             |                     |

NPD = No Performance Determined

MDV = Manufacturer's Declared Value

MLV = Manufacturer's Limiting Value

In accordance with EN 13956:2012 the classification of the product in accordance with EN 13501-5 is limited to class F.

Classifications of roof build-ups B<sub>ROOF</sub>(t1,t2,t4) can be obtained separately.

## 8. Declaration

The performance of the product is in conformity with the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Värnamo, 24-02-2020



Jörgen Skärin  
R&D SealEco AB