



DECLARATION OF PERFORMANCE

RubberTop Flex

N° DOP RubberTop Flex-2020.10.02

1. Unique identification code of the product type:

RubberTop Flex.

2. Identification of the construction product:

See product label and/or packaging.

3. Intended use or uses:

RubberTop Flex flashing tape can be used where a waterproof barrier must be made over an cavity of a double wall or as a flashing element on the roof.

4. Contact address of manufacturer/trading company:

SealEco AB
P.O.Box 514
SE-331 25 Värnamo
Sweden

5. System or systems of assessment and constancy of performance:

System 3.

6. Notified body / Certification n°:

Notified body Number: 1434, 1454, 1488
FPC: 1434-CPR-0254.

7. Declared performance

Characteristic	Test method	Unit	Performance		Harmonised Standard
			Value	Expr. of result	
Water tightness	EN 1928 (B)	10 kPa	Pass	Pass/Fail	EN 13956
Tensile strength L/T	EN 12311-2	N/50 mm	L 160 / T 290	≥ MLV	
Elongation at break L/T	EN 12311-2 (B)	%	L 48 / T 12	≥ MLV	
Resistance to static load	EN 12730 (A/B)	kg	5	≥ MLV	
Resistance to impact	EN 12691 (B)	mm	200	≥ MLV	
Tear resistance L/T	EN 12310-2	N	L 55 / T 80	≥ MLV	
Peel strength of joint	EN 12316-2	N/50 mm	5	≥ MLV	
Shear strength of joint	EN 12317-2	N/50 mm	50 along 62 cross	≥ MLV	
UV resistance		3 000 h	Pass	Pass/Fail	
Foldability	EN 495-5	°C	-40	> MLV	
Reaction to fire	EN 13501-1		Class E	Classification	
Dangerous substances	EU construction directive		NPD	NPD	

NPD = No Performance Determined
MLV = Manufacturer's Limiting Value

8. Declaration

The performance of the product is in conformity with the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Värnamo, 2-10-2020



Jörgen Skärin
R&D SealEco AB