

# TECHNICAL DATA SHEET

## CLEANING WASH 9700

Cleaning Wash 9700 is a technical petrol used for cleaning weathered rubber membranes before installation and repair.

### Technical data

|                           |  |
|---------------------------|--|
| <b>Base:</b>              | Naphtha (petroleum), hydrogen processed light 100%   |
| <b>Colour:</b>            | Colourless liquid  |
| <b>Flash point:</b>       | < 0°C  |
| <b>Density (at 20°C):</b> | 690-720 kg/m <sup>3</sup>  |
| <b>Shelflife:</b>         | 24 months stored dry and in unopened package. Storage limitation due top evaporation and not the quality of the cleaning liquid. |



| Volume (L/package) | Weight (kg/pcs.) |
|--------------------|------------------|
| 1                  | 0.7              |
| 5                  | 3.5              |

### Coverage

5-10 m<sup>2</sup>/litre, depending on the substrate.

### Direction of use

Cleaning Wash 9700 is used for cleaning of membranes and other surfaces prior to splicing, this in cases where the surface is not dry and clean.

### Warning

Cleaning Wash 9700 is highly flammable. Keep away from open fire.

### Note

Please read the MSDS before use.

### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com)