

TECHNICAL DATA SHEET

CLADSEAL EXT

CladSeal EXT is an elastomeric waterproofing strip based on the rubber polymer EPDM. The product is used as a vapour control layer such as façade waterproofing, damp proof course or similar. The product comes in black colour and has a surface texture on both sides for maximum adhesion. CladSeal EXT provide very long expected service life and is an environmental friendly product.



Technical data

Thickness (mm)	Weight (kg/m ²)	Sd-value (m)	Width (mm)	Length (m)
0.6	0.8	19.2	Specified, from 50 to 1700	25
0.75	1.0	24.0	Specified, from 50 to 1700	25
1.0	1.3	32.0	Specified, from 50 to 1700	25
1.1	1.4	35.2	Specified, from 50 to 1700	25
1.2	1.6	38.4	Specified, from 50 to 1700	25
1.3	1.7	41.6	Specified, from 50 to 1700	25
1.5	1.9	48.0	Specified, from 50 to 1700	25

Availability depending on country. Please contact your local supplier for more information.

Packaging

Material will be stacked on pallets 1200 x 800 mm.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

Approvals, Certificates & Specifications

CE: EN 14909, CE: EN 13984. ATG approval for thicknesses 0.6 - 1.5 mm.



Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.