

# TECHNICAL DATA SHEET

## CLADSEAL INT+

CladSeal INT+ is an elastomeric waterproofing strip based on the rubber polymer Butyl with a high water vapour transmission factor. The product is used as a vapour control layer such as façade waterproofing, damp proof course or similar. The product comes in black colour and has a surface texture on both sides for maximum adhesion. CladSeal INT+ provide very long expected service life and is an environmental friendly product.



### Technical data

| Thickness (mm) | Weight (kg/m <sup>2</sup> ) | Sd-value (m) | Width (mm)                 | Length (m) |
|----------------|-----------------------------|--------------|----------------------------|------------|
| 0.75           | 0.9                         | 225          | Specified, from 50 to 1700 | 25         |
| 1.0            | 1.2                         | 300          | Specified, from 50 to 1700 | 25         |

Availability depending on country. Please contact your local supplier for more information.

### Packaging

Material will be stacked on pallets 1200 x 800 mm.

### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

### Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

### Approvals, Certificates & Specifications

CE: EN 14909, CE: EN 13984.



### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).