

# TECHNICAL DATA SHEET

## PRELASTI FLEECE FR

Prelasti Fleece FR is a fleece backed EPDM roofing membrane to be used for exposed roofs either mechanically attached or adhered to substrate with adhesives or bonding bitumen. Seaming is performed with cold Tape Splicing technique.

The product has external fire performance classification  
B<sub>ROOF</sub> (t1,t2,t4).



### Technical data

| Thickness | Thickness EPDM | Weight                |
|-----------|----------------|-----------------------|
| 2.1 mm    | 1.1 mm         | 1.8 kg/m <sup>2</sup> |

| Article            | Thickness (mm) | Width (mm) | Length (m) | Seam type |
|--------------------|----------------|------------|------------|-----------|
| Prelasti Fleece FR | 2.1            | 1 710      | 20         | No edge   |
| Prelasti Fleece FR | 2.1            | 1 710      | 60         | No edge   |

Availability depending on country. Please contact your local supplier for more information.

### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

### Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

### Approvals, Certificates & Specifications

CE: EN 13956, BBA.

B<sub>ROOF</sub> (t1, t2, t4) classifications on demand.



### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com)