

TECHNICAL DATA SHEET

RUBBERSHELL SA-FR 2.5

RubberShell SA-FR 2.5 is an elastomeric EPDM waterproofing membrane, scrim-reinforced with internal glass fibers. The product is also laminated with a self-adhesive bituminous backing, covered by an anti-adhesive protection film. Range of use is as roof waterproofing on low slope roofs. It is adhered to substrate and has a surface texture on the exposed side.



Technical data

Product	Thickness (mm)	Weight (kg/m ²)	Width (mm)	Length (m)	Packaging (rolls/EU-pallet)
RubberShell SA-FR	2.5	2.9	850	10	24
RubberShell SA-FR	2.5	2.9	1700	10	15*

*Packed on pallet 1200 mm x 1750 mm.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. All rolls must be stored and transported in a vertical position (except versions in width 1200 mm or wider). Maximum shelf life is 12 months in unopened packaging.

Approvals, Certificates & Specifications

CE: EN 13956:2012.

ATG approval

Fire classification B_{ROOF} (t1, t2, t4). More information available upon request.



Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.