

# TECHNICAL DATA SHEET

## EPDM COVER TAPE

Cover Tape is made of a cured EPDM laminated with a selfadhesive uncured rubber, and is used for connecting and joining SealEco EPDM membranes. It can also be used for repairs and details in two dimensions and covering mechanically fastened bars. Cover Tape is flexible and provides immediate adhesion when in contact with the membrane. The product should always be used in conjunction with Single Ply Primer.

### Technical data

<b>Base:</b>	Synthetic Rubber
<b>Colour:</b>	Black
<b>Thickness:</b>	1.8 ± 10% mm
<b>Cold bending temperature:</b>	-40°C
<b>Elongation at break:</b>	> 300%
<b>Shelflife:</b>	9 months in original packaging when stored in a dry and cool place (5°C-30°C).



Width (mm)	Roll length (m)	Rolls/case (pcs)	Weight/case (kg)	Cases/pallet (pcs)
152	30.5	2	23.6	18
229	30.5	1	17.7	36
305	15.25	1	12.2	36
457	15.25	1	17.2	24

Availability depending on country. Please contact your local supplier for more information.

### Directions for use

The EPDM membranes to be connected should be dry, clean and free from creases or tension. If necessary, the EPDM membrane can be cleaned with Cleaning Wash 9700 before joining.

Using a marker pen or chalk, mark the position of the location of the Cover Tape. Apply Single Ply Primer with a scrub pad over the entire area to be joined. Wait for the primer to flash off but still tacky. Do not leave exposed for longer than 20 minutes (at 20°C, 50% RV).

Unroll the Cover Tape and press firmly using a 40 mm wide silicone roller. Apply pressure from the middle of the tape to the edge to eliminate any trapped air. Seal all cut edges with Sealant 5590.

Cover Tape shall not be installed in temperatures below +5°C and above 40°C; during rain, mist or where there is a risk of condensation or strong winds. When applied between 5°C and 15°C SealEco recommends to store the Cover Tape in ambient temperatures prior to use.

Consult our installation manuals for more information.

### Note

Please read the MSDS before use.

### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).