

TECHNICAL DATA SHEET

SINGLE PLY PRIMER

Single Ply Primer is used to prime SealEco EPDM membranes to provide a good adhesion between Seam Tape, Flashing Tape or Cover Tape and SealEco membranes. It can also be used to prime substrates such as concrete, plywood, OSB and metal.

Technical data

Base:	Synthetic Rubber solution
Colour:	White/transparent
Solids Content:	Ca 15%
VOC content:	<0.69 kg/l
Specific weight:	0.78 kg/l
Flashpoint:	> -7.8 °C
Consumption:	150-200 g/m ²
Shelf life	12 months when unopened in original packaging. Store in a cool, dry and well ventilated place between 5°C and 30°C



Accessories

Weight (kg/can)	Content (L/can)	Cans/box (pcs)	Boxes/pallet (pcs)
0.9	0.95	6	48
3.5	3.8	6	30



Scrub Held Handle



Scrub Pad

Availability depending on country. Please contact your local supplier for more information.

Coverage

150-200 g/m²

Directions for use

Using a drill or mixer, mechanically stir the Single Ply Primer before use and every 20 minutes once in use. Once stirred the Single Ply Primer, the consistency should change and appear cloudy. The product shall never be diluted and the substrate must be dry and clean. If required, prior to splicing, the EPDM membrane can be cleaned with Cleaning Wash 9700. Do not stretch the joint and ensure it is smooth and free from creases. Carefully apply the Single Ply Primer using a scrub pad and once applied, leave it uncovered until it has flashed off. Do not leave the product open for longer than maximum 20 minutes at 20°C and 50% relative humidity. The tape splicing will obtain its full strength after 48 hours once the surface has completely dried out. Seal the can after use. A scrub pad can be used for 30 m splice. When it has dried out, do not reuse, or clean it. Follow carefully the installation instructions.

The product must not be applied in temperatures below +5°C and above +30°C. Never apply Single Ply Primer in full sun, protect it from the sun during drying time. Stop immediately in case of any precipitation, risk for condensation, mist or heavy winds.

Suitable substrates

Single Ply Primer can be used on SealEco EPDM membranes and most building materials, like bricks, concrete, wood and metals. The substrate must be clean, free of dust and degreased. It is not compatible with PVC, EPS and XPS.

Note

Only for professional use.

Single Ply Primer contains solvents and is highly flammable. Please read MSDS before use.

Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com