

# TECHNICAL DATA SHEET

## PREFABRICATION

### RUBBERTOP FR/FRT/FRTT

RubberTop FR/FRT/FRTT is an elastomeric waterproofing membrane based on the rubber polymer EPDM. RubberTop FR/FRT/FRTT shall be used as a waterproofing layer in roof constructions under ballast or adhered to the substrate, and for greenroofs. RubberTop FR/FRT/FRTT is flame retardant and classified as B<sub>ROOF</sub> (t1, t2, t4). RubberTop FR/FRT/FRTT provides a very long expected service life and is an environmentally friendly product.



#### Technical data

Thickness	Weight
1.2 mm	1.5 kg/m <sup>2</sup>
1.5 mm	1.9 kg/m <sup>2</sup>

#### Rolls, RubberTop FR

With RubberTop FR, prefabrication should be performed with hotbond.

Thickness (mm)	Width (m)	Length (m)
1.2	1.70	25 / 80
1.5	1.70	25 / 65

#### Rolls, RubberTop FRT/FRTT

With RubberTop FRT/FRTT, prefabrication should be performed with hot air or hot wedge technology.

Thickness (mm)	Width (m)	Length (m)
1.2	1.70	25 / 80
1.5	1.70	25 / 65

#### Standard panels

Article	Thickness (mm)	Width (m)	Length (m)
RubberTop FRTT	1.2 / 1.5	3.36 / 5.02 / 6.68 / 8.34 / 10.00 / 11.66 / 13.32 / 14.98	25

#### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

#### Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

#### Approvals, Certificates & Specifications

CE: EN 13956, BBA. Fire classification B<sub>ROOF</sub>(t1, t2, t4) More approvals are available upon request.



#### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).