

# TECHNICAL DATA SHEET

## RUBBERTOP FR

RubberTop FR is an elastomeric waterproofing membrane based on the rubber polymer EPDM. RubberTop FR is used as a waterproofing layer on roof constructions; under ballast, green roofs or adhered to the substrate, and is suitable for both new build and refurbishment projects. The prefabricated panels provide a quicker and safer installation. RubberTop FR is flame retardant and classified as B<sub>ROOF</sub> (t1, t2, t4). RubberTop FR provides a very long expected service life and is an environmentally friendly product.



### Technical data

Thickness	Weight
1.2 mm	1.5 kg/m <sup>2</sup>
1.5 mm	1.9 kg /m <sup>2</sup>

Article	Thickness (mm)	Width (m)	Length (m)
Standard panel RubberTop FR	1.2 / 1.5	3.36 / 5.02 / 6.68 / 8.34 / 10.00 / 11.66 / 13.32 / 14.98	30 / 60
Customer specific 2D membrane RubberTop	1.2 / 1.5	Specified by customer	Specified by customer
Customer specific 3D membrane RubberTop	1.2 / 1.5	Specified by customer	Specified by customer
Strips RubberTop FR	1.2 / 1.5	20 – 1700 (mm)	30

Availability depending on country. Please contact your local supplier for more information.

### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

### Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

### Approvals, Certificates & Specifications

CE: EN 13956, BBA. Fire classification B<sub>ROOF</sub> (t1, t2, t4). More approvals are available upon request.



### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).