

TECHNICAL DATA SHEET

EPDM PE DRAIN

Roof drain in polyethylene (HDPE) with an EPDM flange. The drain can be secured to SealEco EPDM roof membranes with Flashing Tape.



Technical data

Type of tube:	Polyethylene HDPE
Thickness tube:	Min. 3 mm; depending on the diameter
EPDM type:	RubberTop
Thickness EPDM:	1.2 mm
Colour:	Black
Shelf life:	Store cool and dry in the original packaging. There are no limitations in shelf life.

Packaging

Diameter (mm)	Length (mm)	Flap (mm)	Discharge flow rate (L/sec.) (*)	Packaging (pcs/box)	
32	500	280 x 280	to be determined	25	
40	500	280 x 280	to be determined	25	
50	500	280 x 280	to be determined	20	
56	500	280 x 280	to be determined	18	
63	500	280 x 280	to be determined	15	
75	500	280 x 280	to be determined	15	
90	500	280 x 280	5.2	12	
110	500	400 x 400	8.9	9	
125	500	400 x 400	to be determined	9	
160	500	500 x 500	to be determined	4	
200	500	500 x 500	to be determined	4	
250	500	500 x 500	to be determined	4	

Availability depending on country. Please contact your local supplier for more information. (*) Vertical drainage.

Directions for use

Follow all guidelines as described in the manual of the relevant EPDM system.

Suitable substrates

An EPDM PE Drain can only be used on SealEco EPDM membranes. All surfaces to be connected must be clean and dry. If the EPDM has oxidized, it should be grinded with a nylon brush and cleaned, before splicing.

The EPDM PE Drain cannot be installed in temperatures below +5°C and above 30°C; during rain, mist or where there is a risk of condensation or strong winds. When applied between +5°C and 15°C SealEco recommends to store the drain and the adhesives at room temperatures prior to use. Consult our installation manuals for more information.

Note

Read the safety data sheet (MSDS) before usage.

Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.

SealEco | PO Box 514-SE331 25 | Värnamo, Sweden | Telephone: +46 (0)370 510 100 | E-mail: info@sealeco.com | Internet: www.sealeco.com