

TECHNICAL DATA SHEET

EPDM PIPE BOOT

EPDM Pipe Boots are used for sealing pipe penetrations. The product has a flexible EPDM flange which can be secured to SealEco EPDM roof membranes with Flashing Tape.



Technical data

Flange:	EPDM 1.2 mm
Pipe:	EPDM 1.2 mm
Colour:	Black
Shelf life:	Store cool and dry in the original packaging. There are no limitations in shelf life.

Packaging

Product	Diameter (mm)	Height (mm)	Flange (mm)	Packaging (pcs/box)
EPDM Pipe Boot	30	400	400x400	25
	40	400	400x400	25
	50	400	400x400	25
	60	400	400x400	25
	75	400	400x400	25
	80	400	400x400	25
	90	400	400x400	25
	100	400	400x400	25
	110	400	500x500	25
	125	400	500x500	25
	140	400	500x500	25
	160	400	500x500	25
	200	400	500x500	1
	250	400	500x500	1
	300	400	500x500	1

Availability depending on country. Please contact your local supplier for more information.

Directions for use

Follow all guidelines as described in the manual of the relevant EPDM system.

The EPDM membrane should be correctly fastened to the substrate before sealing the pipe penetration. Choose the correct size, to avoid convection, and condensation. The boot should fit perfectly. The EPDM flange will be secured to the EPDM roof membrane with Flashing Tape. Once the pipe boot is correctly spliced, secure the top with a clamping ring and seal with Sealant 5590. Consult our installation manuals for more information.

Suitable substrates

An EPDM Pipe Boot can only be used on SealEco EPDM membranes. All surfaces to be connected must be clean and dry. If the EPDM has oxidized, it should be grinded with a nylon brush and cleaned, before splicing. The EPDM Pipe Boot cannot be installed in temperatures below +5°C and above 30°C; during rain, mist or where there is a risk of condensation or strong winds. When applied between +5°C and 15°C SealEco recommends to store the pipe boot and the adhesives at room temperatures prior to use.

Note

Read the safety data sheet (MSDS) before usage.

Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.