

TECHNICAL DATA SHEET

THERMOBOND SPLICE STRIP

The Thermobond Splice Strip is used for making round shaped details like pipe boots or outlets. The product is built up by a top layer of EPDM and a bottom layer of Thermobond that can be melted for splicing.



Technical data

Reinforcement:	None
Thickness:	1.5 mm
Colour:	Black
Shelf life:	Store cool and dry in the original packaging. There are no limitations in shelf life.

Packaging

Width (mm)	Thickness (mm)	Length (m)	Weight (kg/roll)	Max roll/pallet (pcs)
100	1.5	20	3.9	15x12
150	1.5	20	5.9	15x8
200	1.5	20	7.8	15x6
450	1.5	20	17.6	15x2
600	1.5	20	23.4	15x2
900	1.5	20	35.1	15x1

Availability depending on country. Contact your local supplier for more information.

Directions for use

Thermobond Splice Strip are used for making round shaped details and outlets. For lining applications Thermobond Splice Strip is used for making details and splices. Thermobond seaming technique is unique and patented by SealEco, and can only be used on SealEco EPDM membranes. Thermobond is based on a thermoplastic rubber that can be seamed with conventional seaming methods for plastic material like hot air or hot wedge seaming. The Thermobond material is the base for a full range of accessories that gives good system solutions combining the unique properties of an elastomeric membrane with the seaming properties of the thermoplastics. Installations with Thermobond splicing are only authorised for installers fully trained by SealEco. Consult the instruction manual before use.

Splicing conditions

Thermobond splicing can only be done on SealEco EPDM membranes. The EPDM membrane has to be clean and dry. Oxidised surfaces have to be grinded and cleaned with Cleaning Wash 9700. Splicing is possible between -15°C and 40°C. Splicing is not allowed during precipitation.

Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.