

# TECHNICAL DATA SHEET

## CLEANING WASH 9700

Cleaning Wash 9700 is a technical petrol used for cleaning weathered rubber membranes before installation and repair. Cleaning Wash 9700 can also be used for cleaning tools.



### Technical data

<b>Base:</b>	Naphta (petroleum), light processed hydrogen 100%
<b>Colour:</b>	Colourless
<b>Consistency:</b>	Liquid
<b>Flash point:</b>	< -18°C
<b>Density (à 20°C):</b>	684 g/cm <sup>3</sup>
<b>Shelf life:</b>	24 months in unopened packaging in a well ventilated and dry storage place at temperatures in between +5°C and 30°C.

### Packaging

Volume (L/piece)	Weight (kg/piece)
0.5	0.35
1	0.7

Availability depending on country. Please contact your local supplier for more information.

### Coverage

5 - 10 m<sup>2</sup>/litre, depending on the substrate.

### Directions for use

Cleaning Wash 9700 is used for cleaning contaminated membranes and other surfaces prior to splicing. The cleaner is applied to a cloth that will be used to clean the surface. In case of oxidisation, the splice areas must be grinded with a nylon grinding disc.

Cleaning Wash 9700 can also be used for cleaning tools.

Close the box immediately after use to prevent the cleaner from evaporating.

### Note

Cleaning Wash 9700 is highly flammable. Read the safety data sheet (MSDS) before transport, storage and usage.

### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).