

TECHNICAL DATA SHEET

REINFORCED PERIMETER STRIP

Reinforced Perimeter Strip is used as a base tie-in for unbacked SealEco EPDM roofing membranes. The reinforced EPDM strip is partially coated with a Seam Tape and provides immediate adhesion to the EPDM membrane. Reinforced Perimeter Strip should always be used in conjunction with Single Ply Primer.



Technical data

Base:	Synthetic Rubber
Colour:	Black
Thickness EPDM:	1.14 mm
Width EPDM:	152 mm
Tape thickness:	0.9 mm
Tape width:	76 mm
Shelf life:	12 months in a well ventilated and dry storage place at temperatures in between +5°C and 30°C.

Packaging

Width (mm)	Roll length (m)	Rolls/case (pcs)	Weight/case (kg)	Cases/pallet (pcs)
152	30.48	2	19.0	36

Availability depending on country. Please contact your local supplier for more information.

Directions for use

The EPDM membranes to be connected should be clean, dry and free from creases or tension. If necessary, the EPDM membrane can be cleaned with Cleaning Wash 9700 before joining. Unroll the Reinforced Perimeter Strip alongside the upstand. Position the part of the strip without tape against, or right next to, the upstand and fix it mechanically every 200 mm center to center in the substrate by using the correct screws and pressure plates or Battenbars. The fasteners should not be positioned more than 50 mm away from a roof detail or the upstand. Position and fold back the membrane as close as possible to the tape side of the Reinforced Perimeter Strip. Make sure the membrane is perfectly aligned alongside the tape and apply Single Ply Primer on the membrane corresponding with the tape area. Wait until Single Ply Primer has flashed off. Do not leave exposed for longer than 20 minutes (at 20°C, 50% RH). When flashed off remove the protection foil from the tape and adhere the membrane on the tape side of the Reinforced Perimeter Strip. Mate by hand while doing so and firmly roll with a silicone pressure roller afterwards. First across, than in the length of the tape to avoid trapped air.

Reinforced Perimeter Strip should not be installed in temperatures below +5°C and above 30°C; during rain, mist or where there is a risk of condensation or strong winds. When applied between +5°C and 15°C SealEco recommends to store the Reinforced Perimeter Strip at room temperatures prior to use.

Consult our installation manuals for more information.

Note

Read the safety data sheet (MSDS) before usage.

Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.