



DECLARATION OF PERFORMANCE

Prelasti Green

N° DOP Prelasti Green-2020.02.24

1. Unique identification code of the product type:

Prelasti Green.

2. Identification of the construction product:

See product label and/or packaging.

3. Intended use or uses:

Prelasti Green is an unreinforced EPDM waterproofing membrane produced in two ply. Prelasti Green is high grade EPDM membrane produced out of a compound with recycled ingredients. The product comes in black colour and has a surface texture on both sides. The range of use is roof waterproofing.

4. Contact address of manufacturer/trading company:

SealEco AB
P.O.Box 514
SE-331 25 Värnamo
Sweden

5. System or systems of assessment and constancy of performance:

System 2+.

6. Notified body / Certification n°:

Notified body: 0958 SGS INTRON Certificatie BV
FPC: 0958-CPR-2036/1

7. Declared performance

Characteristic	Test method	Unit	Performance		Harmonised standard
			Value	Expr. of result	
Water tightness	EN 1928 (B)	10 kPa	Pass	Pass/Fail	EN 13956:2012
Tensile strength	EN 12311-2 (B)	N/mm ²	9	≥ MLV	
Elongation at break	EN 12311-2 (B)	%	400	≥ MLV	
Root resistance	EN 13948/FLL		NPD	Pass/Fail	
Resistance to static load	EN 12730 (A/B)	kg	20	≥ MLV	
Resistance to impact	EN 12691 (A/B)	mm	A: 200 B: 2000	≥ MLV	
Tear resistance	EN 12310-2	N	1.2 mm ≥ 75	≥ MLV	
Peel strength of joint	EN 12316-2	N/50 mm	100	≥ MLV	
Shear strength of joint	EN 12317-2	N/50 mm	200	≥ MLV	
Durability	EN 1297	Classification	Pass	Pass/Fail	
Foldability	EN 495-5	°C	-40	> MLV	
External fire performance	EN 13501-5		F _{ROOF} (t)	Classification	
Reaction to fire	EN 13501-1		Class E	Classification	
Dangerous substances	EU construction directive		No dangerous substances	MDV	

NPD = No Performance Determined
 MDV= Manufacturer's Declared Value
 MLV = Manufacturer's Limiting Value

8. Declaration

The performance of the product is in conformity with the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Värnamo, 24-02-2020



Jörgen Skärin
 R&D SealEco AB