

TECHNICAL DATA SHEET

CLADSEAL SA

CladSeal SA is a self adhesive sealing strip against water, based on the rubber EPDM. The product is built by 0.8 mm of scrim-reinforced EPDM membrane coated with 0.5 mm of self adhesive butyl which is covered by a release foil. EPDM and self adhesive butyl gives an extremely high resistance against water vapour. The product is used as a vapour barrier against water, moisture, etc. CladSeal SA is delivered in black colour and has a very long expected life time with a small environmental impact.



Technical data

Total thickness:	1.3 mm
Thickness EPDM:	0.8 mm
Thickness butyl:	0.5 mm
Colour:	Black
Weight:	1.94 kg/m ²
Length:	20 m
Width:	Specified, from 100 to 1700 mm
Sd-value:	2 600 m

Availability depending on country. Please contact your local supplier for more information.

Packaging

Material will be stacked on pallets 1200 x 800 mm.

Directions for use

CladSeal SA can be applied in temperatures between +5°C and 40°C. At temperatures below 10°C, we recommend storing the product at room temperature until required. The surface to be covered should be clean, dry, smooth and free from dust and grease. Primer 9800 must be applied prior to application. In case of porous substrates, a second layer has to be applied. CladSeal SA should be mechanically secured to avoid sliding. Roll out the CladSeal SA with a seam overlap of 80 mm minimum. Remove the release film and press firmly onto the surface. Overlaps have to be spliced with Paste Adhesive 3300 or Contact Adhesive 5000. For more information contact SealEco technical department.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store upright, cool and dry in the original packaging. Shelf life: 18 months.

Approvals, Certificates & Specifications

CE: EN 14909, EN 13984



Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.