

# TECHNICAL DATA SHEET

## PRELASTI FR

Prelasti FR is an elastomeric waterproofing membrane based on the rubber polymer EPDM. Prelasti FR shall be used as waterproofing layer in roof constructions under ballast, mechanical attached or adhered to the substrate. The prefabricated panels provides quicker and safer installation.

Prelasti FR is flame retardant and classified as B<sub>ROOF</sub> (t1, t2, t4). Prelasti FR provide very long expected service life and is an environmentally friendly product.



### Technical data

Thickness	Weight
1.2 mm	1.5 kg/m <sup>2</sup>
1.5 mm	1.9 kg/m <sup>2</sup>

Article	Thickness (mm)	Width (m)	Length (m)
Standard panel Prelasti FR	1.2 / 1.5	3.36 / 5.02 / 6.68 / 8.34 / 10.00 / 11.66 / 13.32 / 14.98	30 / 60
Customer specific 2D membrane Prelasti FR	1.2 / 1.5	Specified by costumer	Specified by costumer
Customer specific 3D membrane Prelasti FR	1.2 / 1.5	Specified by costumer	Specified by costumer
Strips Prelasti FR	1.2 / 1.5	20 – 1700 (mm)	30

Availability depending on country. Please contact your local supplier for more information.

### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

### Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

### Approvals, Certificats & Specifications

CE: EN 13956, KOMO, BBA, Dubokeur, ATG. More approvals are available upon request.



### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).