

TECHNICAL DATA SHEET

PRELASTI GREEN

Prelasti Green is an elastomeric waterproofing membrane based on the rubber polymer EPDM. The membrane is available in standard panels or can be made to measure. It is used as a waterproofing layer in roof constructions; under ballast, green roofs, mechanically fastened or adhered to the substrate.

Prelasti Green consists of 42% recycled material and offers an exceptionally long life.



Technical data

Thickness	Weight
1.2 mm	1.4 kg/m ²

Article	Thickness (mm)	Width (m)	Length (m)
Standard panel Prelasti Green	1.2	3.36 / 5.02 / 6.68 / 8.34 / 10.00 / 11.66 / 13.32 / 14.98	30 / 60
Customer specific 2D membrane Prelasti Green	1.2	Specified by customer	Specified by customer
Customer specific 3D membrane Prelasti Green	1.2	Specified by customer	Specified by customer
Strips Prelasti Green	1.2	20 – 1700 (mm)	30

Availability depending on country. Please contact your local supplier for more information.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

Approvals, Certificates & Specifications

CE: EN 13956



Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.