

TECHNICAL DATA SHEET

RUBBERSHELL SA 1.6

RubberShell SA 1.6 is a two-ply EPDM membrane, scrim-reinforced with internal glassfibers. The product is laminated with a self-adhesive bituminous backing, covered by an anti-adhesive protection film. The product is used in gutters, as a vapour control layer such as façade waterproofing, damp proof course or similar.

It is adhered to substrate with Primer 9800 and has a surface texture on the exposed side.

Seaming is done with hot air.



Technical data

Product	Thickness (mm)	Weight (kg/m ²)	Width (mm)	Length (m)	Packaging
RubberShell SA	1.6	1.9	200	10	84
RubberShell SA	1.6	1.9	400	10	56
RubberShell SA	1.6	1.9	600	10	28
RubberShell SA	1.6	1.9	800	10	28
RubberShell SA	1.6	1.9	1000	10	28
RubberShell SA	1.6	1.9	1600	10	21*

Availability and packaging amount depending on country. Please contact your local supplier for more information.

Packaging

Material will be stacked on pallets 1200 x 800 mm.

*Packed on pallet 1200 mm x 1750 mm.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store vertically, cool and dry in the original packaging.

Shelf life: 12 months in an unopened packaging.

Approvals, Certificates & Specifications

CE: EN 13967, CE: EN 14909, CE: EN 13984



Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.