

# TECHNICAL DATA SHEET

## RUBBERSHELL SA-FR 2.5

RubberShell SA-FR 2.5 is an elastomeric EPDM waterproofing membrane, scrim-reinforced with internal glass fibres. The product is also laminated with a self-adhesive bituminous backing, covered by an anti-adhesive protection film. Range of use is as roof waterproofing on low slope roofs. It is adhered to substrate with Primer 9800 and has a surface texture on the exposed side.

All seaming is done with hot air.

The product has external fire performance classification

B<sub>ROOF</sub> (t1, t2, t4).



### Technical data

Product	Thickness (mm)	Weight (kg/m²)	Width (mm)	Length (m)	Packaging (rolls/EU-pallet)
RubberShell SA-FR	2.5	2.9	850	10	24
RubberShell SA-FR	2.5	2.9	1700	10	15*

Availability depending on country. Please contact your local supplier for more information.

\*Packed on pallet 1200 mm x 1750 mm.

### Physical properties

For detailed product data, please see corresponding Declaration of Performance.

### Storage

Store cool and dry in the original packaging. All rolls must be stored and transported in a vertical position (except versions in width 1200 mm or wider). Maximum shelf life is 12 months in unopened packaging.

### Approvals, Certificates & Specifications

CE: EN 13956:2012.

ATG approval

Fire classification B<sub>ROOF</sub> (t1, t2, t4). More information available upon request.



### Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check [www.sealeco.com](http://www.sealeco.com).