

TECHNICAL DATA SHEET

TOPSKIN GW / LSFR

TopSkin is an elastomeric waterproofing membrane based on the rubber polymer EPDM. TopSkin is used as a waterproofing layer on roof constructions; under ballast, extensive greenroofs or adhered to the substrate, and is suitable for both new build and refurbishment projects. The membrane is available in standard panels. TopSkin GW is an internally scrim-reinforced membrane. TopSkin LSFR has external fire performance classification B_{ROOF} (t1, t2, t4). TopSkin provides a very long expected service life.



Technical data

Thickness	Weight
1.14 mm	1.51 kg/m ²
1.52 mm	2.01 kg/m ²

Article	Thickness (mm)	Width (m)	Length (m)
TopSkin GW	1.14	3.05 / 5.08	30.50
TopSkin GW	1.52	3.05	30.50
TopSkin LSFR	1.14	2.29 / 3.05 / 3.66 / 3.96 / 4.57 / 5.08 / 6.10 / 7.92 / 9.15 / 12.20 / 15.25	30.50
TopSkin LSFR	1.52	3.05 / 5.08 / 9.15	30.50

Availability depending on country. Please contact your local supplier for more information.

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

Approvals, Certificates & Specifications

CE: EN 13956, KOMO.



Disclaimer

Information contained in this data sheet is up-to-date and correct as at the time of issue. For latest version please always check www.sealeco.com.