

DECLARATION OF PERFORMANCE

CladSeal INT-EN14909

N° DOP CladSeal INT-2022.11.28

1. Unique identification code of the product type:

CladSeal INT.

2. Identification of the construction product:

See product label and/or packaging.

3. Intended use or uses:

CladSeal INT is an unreinforced EPDM waterproofing membrane. The product comes in black colour and has a surface texture on both sides. The range of use is damp proof course or similar.

4. Contact address of manufacturer/trading company:

SealEco AB
P.O.Box 514
SE-331 25 Värnamo
Sweden

5. System or systems of assessment and constancy of performance:

System 3.

6. Harmonised standard:

EN 14909:2012

Notified body/ies:

Initial Type Testing was performed by notified body 0402; RISE, Research Institutes of Sweden AB.

7. Declared performance

Characteristic	Test method	Unit	Performance		Harmonised Standard
			Value	Expr. of result	
Watertightness (2 kPa)	EN 1928		Pass	Pass/Fail	EN 14909
Resistance to impact	EN 12691	mm	NPD	≥ MLV	
Durability (artificial ageing) (2 kPa)	EN 1296 EN 1928		Pass	Pass/Fail	
Durability (alkali)	EN 1847 EN 12311-2 (B)	MPa	NPD	≥ MLV	
Reaction to fire	EN 13501-1		Class E	Classification	
Dangerous substances	EU construction directive		No dangerous substance	MDV	

NPD = No Performance Determined
 MDV= Manufacturer's Declared Value
 MLV = Manufacturer's Limiting Value

8. Declaration

The performance of the product is in conformity with the declared performance. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Värnamo, 28-11-2022



Linda Hussami
 Material Engineer
 SealEco AB